VAULT PRIVY INSTALLATION AGREEMENT

To be submitted with the Clark County Sanitary Permit Application

Property Owner
Mailing Address
Location
Lot# CSM/Subdivision ¼ ¼, Sect , T , R E/W, Town:
Tax Parcel Number
Local Description
Legal Description
The following rules apply to a privy sanitation system serving your property:
1. No plumbing shall be connected to the privy.
2. A vault privy shall have a vented, watertight storage chamber of 200 gallons or greater.
(Note: 1 cubic yard [27 cubic feet] = 207 gallons.)
3. The vent serving the storage chamber shall meet the following requirements:
a. Be at least 3 inches in diameter.
b. Vent terminal shall extend at least 8 inches above the roof.
c. Vent terminal shall be 10 feet from any air intake (window, door, soffit vent).
4. The storage chamber shall be anchored to prevent flotation.
5. The following storage chamber setbacks apply:
a. Well25 feet
b. Property line2 feet
c. Navigable water OHWM 75 feet
d. Building ² 5 feet
6. Contents of storage chamber shall removed, transported and disposed per NR 113,
Wisconsin Administrative Code ³ .
7. A <u>public</u> privy shall meet the requirements of SPS 362.2900, Wisconsin Administrative Code.
I, the undersigned, agree to meet the above-mentioned rules for installation and maintenance of the vault privy serving the described property.

Owner's Signature (no stamps)

Date

Owner's Name (please print)

¹Anchor weight = (vault volume in cubic feet X 62.4) – (tank surface area in square feet X 110 X depth of soil cover in feet) – (weight of compartment)

²Building setback. The compartment must be 5 feet or more from the dwelling, the privy structure can be connected to the dwelling. ³A licensed liquid waste carrier must remove and dispose of the vault contents.